

County Surveyor's Record, Douglas County, Oregon

Township 29 South, Range 4 East.
Subdivision.

CHAINS

$\frac{1}{4}$ $\frac{S 18}{S 19}$
1930

from which,

A fir, 40 ins. diam., bears N. 20* E., 25 lks.
dist., marked $\frac{1}{4}$ S 18 B T.

A fir, 10 ins. diam., bears S. 6* W., 65 lks.
dist., marked $\frac{1}{4}$ S 19 B T.

Asc. 25 ft. over SW. slope.

41.00 Spur, bears SW.; desc. 35 ft. over SE. slope.

46.52 Creek, 2 lks. wide, course SW.; asc. 485 ft. over
SW. slope.

69.00 Dim trail, bears NE. and SW.

76.00 Spur, bears S.; desc. 115 ft. over SE. slope to

79.76 The cor. of secs. 17, 18, 19, and 20.

Land; rolling and mountainous.

Soil; sandy, gravelly, and rock, 2nd to 4th rate

Timber; fir, pine, hemlock, and cedar.

Undergrowth; mountain laurel, chinquapin, small fir,
pine, and hemlock.

N. 0*04' W., bet. secs. 17 and 18.

Asc. 210 ft. over S. slope, through medium timber and
medium undergrowth.

9.08 Dim trail, bears NW. and SE.

13.00 Spur, bears SE.; desc. 160 ft. over NE. slope.

30.97 Creek, 1 lk. wide, course E.; asc. 100 ft. over SE.
slope to

40.00 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in
the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked.

$\frac{1}{4}$
S 18 | S 17
1930