

County Surveyor's Record, Douglas County, Oregon

Willamette Meridian through T. 30 S.

As surveyed by Homer D. Angell, Deputy Surveyor,
Under Contract No. 746, dated May 5, 1902.

CHAINS	
	From the cor. of Tp. 30 and 31 S., I run North, bet. secs. 31 and 36.
1.33	A fir, 30 ins. diam., on line I mark with two notches on N. and S. sides.
35.00	A spring branch, 1 lk. course SW.
38.00	A fir, 24 ins. diam., on line, I mark with two notches on N. and S. sides. Difference between measurement of 40.00 chs. by two sets of chainmen is 14 lks, position of middle point By first set, 40.07. By second set, 39.93. The mean of which is
40.00	Set a basalt stone, 15x12x6 ins., 10 ins. in ground for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W. face, from which A fir, 30 ins. diam., bears N.29*E., 22 lks. dist. Marked $\frac{1}{4}$ S 31 B T. A fir, 20 ins. diam., bears S.75*W., 14 lks. dist. Marked $\frac{1}{4}$ S 36 B T.
54.00	Top of divide, 1500 ft. high, bears S.60*E., N.60*W.
58.15	Mountain Trail, bears E. and W. Difference between measurement of 80.00 chs. by two sets of chainmen is 8 lks. position of middle point. By first set, 80.04. By second set, 79.96. The mean of which is
80.00	Set a basalt stone, 20x10x8 ins., 15 ins. in ground, for cor. of secs. 25 and 36, marked with 5 notches on N. and 1 notch on S. edges, from which A fir, 18 ins. diam., bears S.64*W., 32 lks. dist. Marked T 30 S R 1 W S 36 B T. A fir, 18 ins. diam., bears N.10*W., 42 lks. dist. Marked T 30 S R 1 W S 25 B T.
	Land, mountainous. Soil, stoney and third rate. Timber, fir, pine, hemlock. Undergrowth, laurel, willow and huckleberry.