

County Surveyor's Record, Douglas County, Oregon

Willamette Meridian through T. 30 S.

CHAINS	North, bet. secs. 19 and 24.
	Along E. slope through heavy timber and dense undergrowth.
24.70	A spring branch, 1 lk. wide, course E.
36.00	A spring branch, 2 lks. wide, course E.
	Difference between measurement of 40.00 chs. by two sets of chainmen is 8 lks., position of middle point
	By first set, 40.04
	By second set, 39.96
	the mean of which is
40.00	Set a basalt stone, 20x12x5 ins., 15 ins. in ground for
	$\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W. face, from which
	A fir, 12 ins. diam., bears N.20*E., 11 lks. dist.
	Marked $\frac{1}{4}$ S 19 B T.
	A fir, 20 ins. diam., bears W., 3 lks. dist.
	Marked $\frac{1}{4}$ S 24 B T.
74.50	A spring branch, 2 lks. wide, bears NW.
78.40	A spring branch, 1 lk. wide, course NW.
	Difference between measurement of 80.00 chs. by two sets of chainmen is 10 lks. position of middle point
	By first set, 80.05
	By second set, 79.95
	the mean of which is
80.00	Set a basalt stone, 15x8x6 ins., 10 ins. in ground,
	for cor. of secs. 13 and 24, marked with 3 notches on
	N. and S. edges, from which
	A fir, 12 ins. diam., bears S.64*W., 30 lks. dist.
	Marked T 30 S R 1 W S 24 B T.
	A fir, 30 ins. diam., bears N.50*W., 38 lks. dist.
	Marked T 30 S R 1 W S 13 B T.
	From the ^{the} cor. the old sec. cor. for secs. 13, 18, 19 and
	24 bears N. 33*7 ^{N. 83°7' W. 84} , 29.60 chs. dist. The
	stake is completely decayed but is witnessed
	as described by the surveyor general. In the
	place of the stake at the original point, I set