

## County Surveyor's Record, Douglas County, Oregon

Willamette Meridian through T. 30 S.

CHAINS	<p>80.00 Set a basalt stone, 15x12x12 ins., 10 ins. in ground, for cor. of secs. 12 and 13, marked with 2 notches on N. and 4 notches on S. edges, from which</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S.13*W., 106 lks. dist. Marked T 30 S R 1 W.S 13 B T.</p> <p style="padding-left: 40px;">A pine, 20 ins. diam., bears N.48*W., 11 lks. dist. Marked T 30 S R 1 W.S 12 B T.</p> <p>From this cor. the old cor. of secs. 7, 12, 13 and 18 which is a post marked and witnessed as described by the surveyor general, bears N.81*20'W., 29.79 chs. dist. I destroy all marks on this cor. referring to T 30 S R 1 E.</p>
	<p>Land, mountainous.</p> <p>Soil, stoney and third rate.</p> <p>Timber, fir, pine and hemlock.</p> <p>Undergrowth, laurel and huckleberry.</p> <p>Mountainous or heavily timbered land or land covered with dense undergrowth. 80.00 chs.</p>
	<p>North, bet. secs. 7 and 12.</p> <p>Over West slope through heavy timber and scattering undergrowth.</p>
30.00	<p>Thence over almost level ground.</p> <p>Difference between measurement of 40.00 chs. by two sets of chainmen is 16 lks., position of middle point</p> <p style="padding-left: 40px;">By first set, 40.08 by second set, 39.92 the mean of which is</p>
40.00	<p>Set a basalt stone, 15x10x5 ins., 10 ins. in ground, for <math>\frac{1}{4}</math> sec. cor., marked <math>\frac{1}{4}</math> on W. face, from which</p> <p style="padding-left: 40px;">A fir, 60 ins. diam., bears SE., 26 lks. dist. Marked <math>\frac{1}{4}</math> S 7 B T.</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N.80*W., 57 lks. dist. Marked <math>\frac{1}{4}</math> S 12 B T.</p>
75.25	<p>Top of ridge, bears E. and W. Descend.</p> <p>Difference between measurements of 80.00 chs. by two</p>