

County Surveyor's Record, Douglas County, Oregon

Retracement and Dependent Resurvey
of Portion of Subdivisional Lines in T. 30 S., R. 1 W.

CHAINS	<u>Retracement</u>
	From the $\frac{1}{4}$ cor. on the old E. bdy. of sec. 12 South, retracing old E. bdy. of sec. 12.
40.00	After diligent search find no evidence of the old cor. of secs. 12 and 13.
	Thence
	South on old E. bdy. of sec. 13, continuing measurement.
81.16	Fall 47 lks. E. of the $\frac{1}{4}$ sec. cor. on old E. bdy. of sec. 13.
	The bearing and length of this line is S.0°20'W., 81.16 chs. and proportional length of each half mile is 40.58 chs.
	<u>Resurvey</u>
	From the $\frac{1}{4}$ sec. cor. on the old E. bdy. of sec. 12, established by Deputy Hathorn, located by reference to the original bearing trees, which are in agreement with the field notes.
	At exact corner point (no iron post available)
	Set a basalt stone, 24x8x6 ins., 18 ins. in the ground for $\frac{1}{4}$ sec. cor. of original sec. 12, marked $\frac{1}{4}$ S 12 on W. face, from which
	A cedar, 12 ins. diam., bears S.35°W., 15 lks. dist.
	Marked $\frac{1}{4}$ S 12 B T. new B. T.
	A fir, 28 ins. diam., bears N.10°W., 8 lks. dist.
	Marked $\frac{1}{4}$ S 12 B T. old B. T.
	I obliterate marks on former bearing tree intended
	in the original survey to refer to sec. 7, T.
	30 S., R. 1 E.
	S.0°20'W., on a true line on old E. bdy. of sec. 12.
	Over mountainous land, through heavy timber and dense undergrowth.
	Descend 123 ft. over SW. slope.
9.00	Freezeout Creek, 8 lks. wide, course SE. Ascend 33 ft. over NE. slope.
23.00	Descend 62 ft. on gentle SE. slope.
26.33	Creek, 2 lks. wide, course SE.