Retracement and
Dependent Resurvey of Portion of Subdivisional Lines in T. 30 S., R. 1 W.

CHAINS	
40.58	Proportional measurement. Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in ground, for cor. of original secs. 12 and 13, with brass cap marked, T30S S12 S13 R1W 1923 from which A fir, 12 ins. diam., bears S.8½°W., 283 lks. dist. Marked T 30 S R 1 W S 13 B T. An ash, 12 ins. diam., bears N.24¼°W., 174 lks. dist. Marked T 30 S R 1 W S 12 B T. Land, mountainous. Soil, clay loam, stony in places, 1st, 2nd and 3rd rate. Timber, fir, cedar, pine. Undergrowth, hazel, vine maple.
	Thence S.0°20'W., on old E. bdy. of sec. 13. Over mountainous land, through heavy timber and dense undergrowth.
0.97	Spring, flows E.
3.60	Creek, 1 lk. wide, course SE.
5.10	Creek, 1 lk. wide, course SE.
5.80	Creek, 1 lk. wide, course SE.
7.43	Creek, 1 lk. wide, course SE.
	Trail, bears NE. and SW.
	Ascend 93 ft. on NE. slope.
16.00	Spur, slopes SE., descend 465 ft. on general S. slope.
34.77	Draw, course SE.
40.58	The ¼ sec. cor. on old E. bdy. of sec. 13, established by Deputy Hathorn, located by reference to the original bearing trees, which are in agreement with the field notes, except that the W. tree is dead and fallen.