

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Willamette Meridian through T. 30 S.  
As surveyed by Fred Mensch, U. S. Cadastral Engineer  
Under Contract, dated June 7, 1922.

## CHAINS

From the cor. of Tps. 30 and 31 S., R. 1 W., on the Will.  
Meridian, I retrace the Will. Meridian N. through T.  
30 S., finding each half mile to closely agree with the  
original record in bearing and but two half miles to  
disagree in measurement, and I, therefore, adopt the  
original record for this line, except for the two half  
miles as hereinafter shown.

From the cor. of Tps. 30 and 31 S., R. 1 W., on the Will.  
Meridian.

North, on a dependent resurvey of the east boundary of  
Sec. 36, T. 30 S., R. 1 W.

3.58 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the  
ground, for  $\frac{1}{4}$  sec. cor., of sec. 31 only, T. 30 S., R.  
1 E., with brass cap marked

$\frac{1}{4}$ S31  
1923

from which

A fir, 32 ins. diam., bears N.3\*E., 90 lks. dist.

Marked  $\frac{1}{4}$  S 31 B T.

A fir, 20 ins. diam., bears S.3\*E., 30 lks. dist.

Marked  $\frac{1}{4}$  S 31 B T.

40.00 The original  $\frac{1}{4}$  sec. cor., which is a basalt stone,  
12x6x5 ins. above ground, firmly set marked  $\frac{1}{4}$  on W.  
face, hereafter this cor. will refer to sec. 36 only.

I mark the  $\frac{1}{4}$  sec. stone S 36 on W. face, from which

A fir, 30 ins. diam., bears N.29\*E., 22 lks. dist.

I destroy marks on this tree.

A fir, 20 ins. diam., bears S.75\*W., 14 lks. dist.

Marked  $\frac{1}{4}$  S 36 B T., old B. T.

A fir, 36 ins. diam., bears N.23\*W., 26 lks. dist.

Marked  $\frac{1}{4}$  S 36 B T., new B. T.

43.58 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in  
the ground, for cor. of secs. 30 and 31, T. 30 S., R. 1 E.,  
only, with brass cap marked