

County Surveyor's Record, Douglas County, Oregon

13

Dependent Resurvey of Willamette Meridian through T. 30 S.

CHAINS

T30S	T30S
R1W	S30
S36	S31
	R1E
	1923

from which

A fir, 34 ins. diam., bears N.44*E., 25 lks. dist.

Marked T 30 S R 1 E S 30 B T.

A fir, 18 ins. diam., bears S.20*E., 13 lks. dist.

Marked T 30 S R 1 E S 31 B T.

80.00 The cor. of secs. 25 and 36, which is a basalt stone 10x8x5 ins. above ground, firmly set, marked and witnessed as described by the surveyor general. I mark the cor. stone additionally S 36 on SW., and S 25 on NW. face.

North, resurveying the E. bdy. of sec. 25, T. 30 S., R. 1 W.

3.58 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., sec. 30 only, with brass cap marked

	$\frac{1}{4}$ S30
	1923

from which

A fir, 28 ins. diam., bears N.26*E., 19 lks. dist.

Marked $\frac{1}{4}$ S 30 B T.

A fir, 12 ins. diam., bears S.53*E., 27 lks. dist.

Marked $\frac{1}{4}$ S 30 B T.

40.00 The original $\frac{1}{4}$ sec. cor., which is a basalt stone, 12x10x5 ins. above ground, firmly set, marked $\frac{1}{4}$ on W. face. Hereafter this cor. will refer to sec. 25 only, I mark the cor. stone $\frac{1}{4}$ S 25 on W. face, from which

A fir, 30 ins. diam., bears S.17*W., 35 lks. dist.
Marked $\frac{1}{4}$ S 25 B T., new B. T.

A fir, 34 ins. diam., bears N.80*W., 33 lks. dist.
Marked $\frac{1}{4}$ S 25 B T., old B. T.

I destroy the marks on the old B T in sec. 30.