

County Surveyor's Record, Douglas County, Oregon

24

Dependent Resurvey of Willamette Meridian through T. 30 S.

CHAINS

43.58

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for the cor. of secs. 19 and 30, only, with brass cap marked

T30S	T30S
R1W	S19
S25	S30
	R1E
	1923

from which

A madrona, 16 ins. diam., bears N.20*E., 15 lks. dist.

Marked T 30 S R 1 E S 19 B T.

A fir, 14 ins. diam., bears S.68*E., 37 lks. dist.

Marked T 30 S R 1 E S 30 B T.

80.00

The cor. of secs. 24 and 25, which is a basalt stone 10x6x5 ins. above ground, firmly set, marked and witnessed as described by the surveyor general.

I mark the cor. stone S 25 on SW., and S 24 on NW. face.

3.58

North, resurveying the E. bdy. sec. 24, T. 30 S., R. 1 W. Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 19, only, with brass cap marked

$\frac{1}{4}$ S19
1923

from which

A fir, 50 ins. diam., bears N.2*E., 356 lks. dist.

Marked $\frac{1}{4}$ S 19 B T.

A madrona, 6 ins. diam., bears S.5*E., 233 lks. dist.

Marked $\frac{1}{4}$ S 19 B T.

40.00

The original $\frac{1}{4}$ sec. cor., which is a basalt stone, 12x5x5 ins. above ground, firmly set, marked $\frac{1}{4}$ on W. face.

Hereafter this cor. will refer to sec. 24 only.

I mark the cor. stone $\frac{1}{4}$ S 24 on W. face, from which

A fir, 30 ins. diam., bears S.75*W., 3 lks. dist.

Marked $\frac{1}{4}$ S 24 B T., old B. T.

A fir, 30 ins. diam., bears N.58*W., 51 lks. dist.

Marked $\frac{1}{4}$ S 24 B T., new B. T.