

Dependent Resurvey of Willamette Meridian through T. 30 S.

CHAINS											
43.58	<p>I obliterate the marks on the old B T in sec. 19.</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for the cor. of secs. 18 and 19, only, with brass cap marked</p>										
	<table border="0" style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding-right: 5px;">T30S</td> <td style="border-left: 1px solid black; padding-left: 5px;">T30S</td> </tr> <tr> <td style="padding-right: 5px;">R1W</td> <td style="border-left: 1px solid black; padding-left: 5px;">S18</td> </tr> <tr> <td style="padding-right: 5px;">S24</td> <td style="border-left: 1px solid black; padding-left: 5px;">S19</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding-left: 5px;">R1E</td> </tr> <tr> <td></td> <td style="padding-left: 10px;">1923</td> </tr> </table>	T30S	T30S	R1W	S18	S24	S19		R1E		1923
T30S	T30S										
R1W	S18										
S24	S19										
	R1E										
	1923										
	<p>from which</p> <p>A fir, 22 ins. diam., bears N.2*E., 62 lks. dist. Marked T 30 S R 1 E S 18 B T.</p> <p>A fir, 17 ins. diam., bears S.66*E., 18 lks. dist. Marked T 30 S R 1 E S 19 B T.</p>										
80.00	<p>The cor. of secs. 13 and 24 only, which is a basalt stone, 8x6x5 ins. above ground, firmly set, marked and witnessed as described by the surveyor general.</p> <p>I mark the cor. stone S 24 on SW., and S 13 on NW., face.</p>										
	<p>North, resurveying the E. bdy. of sec. 13, T. 30 S., R. 1 W.</p>										
3.58	<p>Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for <math>\frac{1}{4}</math> sec. cor., of sec. 18, only, with brass cap marked</p>										
	<table border="0" style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding-right: 5px;"></td> <td style="border-left: 1px solid black; padding-left: 5px;"><math>\frac{1}{4}</math>S18</td> </tr> <tr> <td></td> <td style="padding-left: 10px;">1923</td> </tr> </table> <p>from which</p> <p>A fir, 60 ins. diam., bears N.62*E., 146 lks. dist. Marked <math>\frac{1}{4}</math> S 18 B T.</p> <p>A fir, 30 ins. diam., bears S.3*E., 124 lks. dist. Marked <math>\frac{1}{4}</math> S 18 B T.</p>		$\frac{1}{4}$ S18		1923						
	$\frac{1}{4}$ S18										
	1923										
40.00	<p>The original <math>\frac{1}{4}</math> sec. cor., which is a basalt stone, 10x6x5 ins. above ground, firmly set, marked <math>\frac{1}{4}</math> on W. face.</p> <p>Hereafter this cor. will refer to sec. 13 only. I mark the cor. stone <math>\frac{1}{4}</math> S 13 on W. face, from which</p> <p>A fir, 30 ins. diam., bears S.3*W., 46 lks. dist. Marked <math>\frac{1}{4}</math> S 13 B T., old B. T.</p>										