

Dependent Resurvey of Willamette Meridian through T. 30 S.

CHAINS	<p>A fir, 12 ins. diam., bears S.80*W., 56 lks. dist. Marked $\frac{1}{4}$ S 12 B T., old B T. A fir, 26 ins. diam., bears N.42*W., 57 lks. dist. Marked $\frac{1}{4}$ S 12 B T., new B T. I obliterate the marks on old B T in sec. 7.</p> <p>43.58 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 6 and 7 only, with brass cap marked</p> <div style="text-align: center;"> <table border="1"> <tr><td>T30S</td><td>T30S</td></tr> <tr><td>R1W</td><td>S6</td></tr> <tr><td>S13</td><td>S7</td></tr> <tr><td></td><td>R1E</td></tr> <tr><td colspan="2">1923</td></tr> </table> </div> <p>from which</p> <p>A fir, 22 ins. diam., bears N.67*E., 85 lks. dist. Marked T 30 S R 1 E S 6 B T. A fir, 48 ins. diam., bears S.75*E., 21 lks. dist. Marked T 30 S R 1 E S 7 B T.</p> <p>79.82 The cor. of secs. 1 and 12 only, which is a basalt stone, 12x8x5 ins. above ground, firmly set, marked and witnessed as described by the surveyor general. Both old bearing trees are dead. I mark the stone S 12 on SW., and S 1 on NW. face, from which</p> <p>A fir, 8 ins. diam., bears S.18*W., 49 lks. dist. Marked T 30 S R 1 W S 12 B T., new B T. A cedar, 24 ins. diam., bears N.31*W., 129 lks. dist. Marked T 30 S R 1 W S 1 B T., new B T.</p>	T30S	T30S	R1W	S6	S13	S7		R1E	1923	
T30S	T30S										
R1W	S6										
S13	S7										
	R1E										
1923											
3.76	<p>North, resurveying the E. bdy. of sec. 1, T. 30 S., R. 1 W. Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 6 only, with brass cap marked</p> <div style="text-align: center;"> <table border="1"> <tr><td>$\frac{1}{4}$S6</td></tr> <tr><td>1923</td></tr> </table> </div> <p>from which</p> <p>A fir, 10 ins. diam., bears N.71*E., 17 lks. dist. Marked $\frac{1}{4}$ S 6 B T. A hemlock, 10 ins. diam., bears S.30*E., 5 lks. dist. Marked $\frac{1}{4}$ S 6 B T.</p>	$\frac{1}{4}$ S6	1923								
$\frac{1}{4}$ S6											
1923											
40.23	<p>The original $\frac{1}{4}$ sec. cor., changed by Deputy Mensch under contract no. 797 to refer sec. 1 only, which is a basalt stone 12x6x5 ins. above ground, firmly set, marked and witnessed as described by the surveyor general. I mark the cor. stone $\frac{1}{4}$ S 1 on W. face.</p>										
44.27	<p>The cor. of Tps. 29 and 30 S., R. 1 E., which is a conglomerate stone 12x10x5 ins. above ground, firmly set, marked and witnessed as described by the surveyor general.</p>										
<p>Retracement and Dependent Resurvey of South Boundary of T. 29 S., R. 1 E.</p>											
<p><u>Retracement</u></p>											
39.21	<p>From the cor. of Tps. 29 and 30 S., R. 1 E., on the Willamette Meridian, East, retracing the south bdy. of sec. 31, T. 29 S., R. 1 E.</p>										
79.36	<p>Intersect the $\frac{1}{4}$ sec. cor. (3.5) Intersect the cor. of secs. 6, 7, 31 and 32.</p> <p style="text-align: center;">-----</p>										