

County Surveyor's Record, Douglas County, Oregon

28

Retracement and Dependent Resurvey of
South Boundary of T. 29 S., R. 1 E.

CHAINS	
0.98	East, retracing the S. bdy. of sec. 32, T. 29 S., R. 1 E. Point of intersection of line bet. secs. 5 and 6, T. 30 S., R. 1 E.
39.90	Intersect the $\frac{1}{4}$ sec. cor.
80.04	Intersect the cor. of secs. 4, 5, 32 and 33.

1.38	East, retracing the S. bdy. of sec. 33, T. 29 S., R. 1 E. Point of intersection of line bet. secs. 4 and 5, T. 30 S., R. 1 E.
39.94	Intersect the $\frac{1}{4}$ sec. cor.
80.00	Intersect the cor. of secs. 3, 4, 33, and 34.

1.44	East, retracing the S. bdy. of sec. 34, T. 29 S., R. 1 E. Point of intersection of line bet. secs. 3 and 4, T. 30 S., R. 1 E. Set a conglomerate stone, 24x14x10 ins., 18 ins. in the ground, for closing cor. of secs. 3 and 4, marked with 3 grooves on E., CC and 6 grooves on S., and 3 grooves on W., face, from which A fir, 20 ins. diam., bears S.10*E., 50 lks. dist. Marked T 30 S R 1 E S 3 C C B T. A fir, 10 ins. diam., bears S.45*W., 22 lks. dist. Marked T 30 S R 1 E S 4 C C B T. No iron post available for this cor. The $\frac{1}{4}$ sec. cor. on S. bdy. of sec. 34, which is a conglomerate stone, 5x8x4 ins. above ground, firmly set, marked and witnessed as described by the surveyor general, bears E. This line not remeasured.
	Dependent Resurvey of S. Bdy. of T. 29 S., R. 1 E.
	<u>Resurvey</u>
	The cor. established for secs. 3, 4, 33, and 34 is a cross (X) on bed-rock, witnessed as described by surveyor general. Hereafter this cor. will refer to secs. 33 and 34 only. I mark the rock S 34 on NE., and S 33 on NW. side of cross and obliterate marks on bearing trees for secs. 3 and 4. Thence West, resurveying the S. bdy. of sec. 33.
38.59	Point for the $\frac{1}{4}$ sec. cor. of sec. 4 only. Set a conglomerate stone 20x12x8 ins., 15 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 4 only, marked $\frac{1}{4}$ S 4 on S. face, from which A fir, 20 ins. diam., bears S.38*E., 37 lks. dist. Marked $\frac{1}{4}$ S 4 B T. A fir, 9 ins. diam., bears S.80*W., 33 lks. dist. Marked $\frac{1}{4}$ S 4 B T. No iron post available for this corner.
40.06	The $\frac{1}{4}$ sec. cor. est. for secs. 4 and 33, which is a conglome- rate stone 8x6x5 ins. above ground, firmly set, marked and witnessed as described by the surveyor general. Hereafter this cor. will refer to sec. 33 only, I mark the cor. stone $\frac{1}{4}$ S 33 on N. face, from which A fir, 6 ins. diam., bears N.23*E., 18 lks. dist. Marked $\frac{1}{4}$ S 33 B T., old B T. A pine, 44 ins. diam., bears N.57*W., 48 lks. dist. Marked $\frac{1}{4}$ S 33 B T., new B T. I obliterate the marks on old B T in sec. 4.
78.62	Point of intersection of line bet. secs. 4 and 5, T. 30 S., R. 1 E., determined as hereinafter set forth. Set a conglomerate stone, 20x14x4 ins., 15 ins. in ground, for closing cor. of secs. 4 and 5, marked with 4 grooves on E., CC and 6 grooves on S., and 2 grooves on W. face, from which