

Dependent Resurvey of S. Bdy. of T. 29 S., R. 1 E.

CHAINS
79.06

I obliterate the marks on the old B T in sec. 8.

Point of intersection of line bet. secs. 5 and 6, T. 30 S.,

R. 1 E., determined as hereinafter set forth.

Set a conglomerate stone, 20x16x7 ins., 15 ins. in the ground, for closing cor. of secs. 5 and 6, marked with

5 grooves on E.,

CC and 6 grooves on S., and

1 groove on W. face, from which

A fir, 16 ins. diam., bears S.18*E., 33 lks. dist.

Marked T 30 S R 1 E S 5 C C B T.

A fir, 14 ins. diam., bears S.18*W., 27 lks. dist.

Marked T 30 S R 1 E S 6 C C B T.

No iron post available for this corner.

80.04

The cor. established for secs. 5, 6, 31 and 32, which

is a basalt stone, 10x8x5 ins. above ground, firmly

set, marked and witnessed as described by the surveyor general.

Hereafter this cor. will refer to secs. 31 and 32 only.

I mark the cor. stone S. 32 on NE., and S 31 on NW. face

and obliterate the marks on old bearing trees S. of line.

39.02

West, resurveying the S. bdy. of sec. 31, T. 29 S., R. 1 E.

Point for the $\frac{1}{4}$ sec. cor. of sec. 6 only.

Set a conglomerate stone, 20x12x5 ins., 15 ins. in the ground, for $\frac{1}{4}$ sec. cor., of sec. 6 only, marked $\frac{1}{4}$ S 6

on S. face, from which

A fir, 18 ins. diam., bears S.57*E., 50 lks. dist.

Marked $\frac{1}{4}$ S 6 B T.

A fir, 18 ins. diam., bears S.73*W., 26 lks. dist.

Marked $\frac{1}{4}$ S 6 B T.

No iron post available for this corner.

40.15

The $\frac{1}{4}$ sec. cor., established for secs. 6 and 31, which is

a conglomerate stone, 10x8x5 ins. above ground, firmly

set, marked and witnessed as described by the surveyor

general.