

Dependent Resurvey of S. Bdy. of T. 29 S., R. 1 E.

CHAINS

Hereafter this cor. will refer to sec. 31 only.

I mark the cor. stone $\frac{1}{4}$ S 31 on N. face, from which

A hemlock, 8 ins. diam., bears N.1*E., 11 lks.

Marked $\frac{1}{4}$ S 31 B T., old B. T.

A cedar, 10 ins. diam., bears N.78*W., 38 lks.

Marked $\frac{1}{4}$ S 31 B T.

I obliterate the marks on the old B T in sec. 6.

79.36

The cor. of Tps. 29 and 30 S., R. 1 E., on the Willamette Meridian, hereinbefore described.

Subdivisions of T. 30 S., R. 1 E.

Same Deputy and Contract

From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., heretofore described.

N.0*02'W.; bet. secs. 33 and 34.

Over mountainous land, through medium heavy timber and dense undergrowth.

Descend 350 ft. over N. slope.

6.50

Bluff, 35 ft. high, faces NW.

9.21

Dark Canyon Creek, 12 lks. wide, comes from SW., course N.

11.74

Leave creek, course NW.

15.00

Foot of rough, rocky SW. slope, ascend 100 ft. to spur.

26.00

Top of bluff, 40 ft. high, faces SW.

29.90

Spur, slopes NW. Descend 410 ft. to

40.00

Set an iron post, 3 ft. long, $\frac{1}{2}$ in. diam., 27 ins. in ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$
S33|S34
1923

from which

A fir, 30 ins. diam., bears S.18*E., 136 lks. dist.

Marked $\frac{1}{4}$ S 34 B T.

A fir, 26 ins. diam., bears S.34*W., 126 lks. dist.

Marked $\frac{1}{4}$ S 33 B T.