

County Surveyor's Record, Douglas County, Oregon

37

Subdivision of T. 30 S., R. 1 E.

CHAINS	
	Descend 400 ft. over NE. slope.
55.50	Draw opens W., ascend 250 ft.
58.70	Bluff, 30 ft. high, faces S.
62.04	Spur slopes NW., descend 300 ft. over NW. slope.
64.00	Enter rock slide, bears NW., and SE.
66.00	Leave same, bears NW. and SE.
76.74	Dark Canyon Creek, 20 lks. wide, course E.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 27, 28, 33 and 34, with brass cap marked
	<div style="text-align: center;"> T30S R1E S28/S27 S33/S34 1923 </div>
	from which
	A fir, 20 ins. diam., bears N.15*E., 12 lks. dist.
	Marked T 30 S R 1 E S 27 B T.
	A fir, 10 ins. diam., bears S.14*E., 46 lks. dist.
	Marked T 30 S R 1 E S 34 B T.
	A pine, 20 ins. diam., bears S.30*W., 47 lks. dist.
	Marked T 30 S R 1 E S 33 B T.
	A fir, 12 ins. diam., bears N.11*W., 48 lks. dist.
	Marked T 30 S R 1 E S 28 B T.
	Land, mountainous.
	Soil, stony, third and fourth rate.
	Timber, fir, hemlock and cedar.
	Undergrowth, vine maple, hazel, and chinquapin.
	<p>N.0*02*W., bet. secs. 27 and 28.</p> <p>Over mountainous land, through medium heavy timber and dense undergrowth.</p> <p>Ascend 25 ft. to</p>
7.00	Top of ascent bears E. and W.
	Descend 150 ft. over rolling NE. slope to
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked