

County Surveyor's Record, Douglas County, Oregon

34

Subdivision of T. 30 S., R. 1 E.

CHAINS

19.90 Spur slopes NE., descend 80 ft. over NW. slope to
 27.80 Foot of descent bears E. and W., ascent 90 ft. over SW.
 slope to
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in
 the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$$\begin{array}{c} \frac{1}{4} \\ \text{S21} | \text{S22} \\ \text{1923} \end{array}$$

from which

A fir, 14 ins. diam., bears S.88*E., 5 lks. dist.

Marked $\frac{1}{4}$ S 22 B T.

A fir, 27 ins. diam., bears N.34*W., 41 lks. dist.

Marked $\frac{1}{4}$ S 21 B T.

Ascend 30 ft. to

42.00 Spur slopes SE., descend 120 ft. over NE. slope to

47.70 Draw opens SE., ascend 40 ft.

61.54 Spur slopes NE., descend 360 ft. over NW. slope to

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in
 the ground for cor. of secs. 15, 16, 21 and 22, with
 brass cap marked

$$\begin{array}{c} \text{T30S R1E} \\ \text{S16} | \text{S15} \\ \text{S21} | \text{S22} \\ \text{1923} \end{array}$$

from which

A fir, 18 ins. diam., bears N.29*E., 22 lks. dist.

Marked T 30 S R 1 E S 15 B T.

A fir, 16 ins. diam., bears S.15*E., 26 lks. dist.

Marked T 30 S R 1 E S 22 B T.

A fir, 18 ins. diam., bears S.83*W., 22 lks. dist.

Marked T 30 S R 1 E S 21 B T.

A fir, 12 ins. diam., bears N.35*W., 7 lks. dist.

Marked T 30 S R 1 E S 16 B T.

Land, mountainous.

Soil, clay loam, second and third rate.

Timber, fir, hemlock, cedar, and pine.

Undergrowth, chinquapin, hazel and vine maple.