

Subdivision of T. 30 S., R. 1 E.

CHAINS

N.0*02'W., bet. secs. 15 and 16.

Over mountainous land, through heavy timber and dense undergrowth.

Descend 150 ft. over NW. slope, to

10.84 Sick Creek, 5 lks. wide, course NE., ascend 30 ft. over SE. slope to

17.70 Spur slopes E., descend 140 ft. to

23.70 Dark Canyon Creek, 20 lks. wide, course NW., ascend 70 ft. over SW. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$
 S16 | S15
 1923

from which

A fir, 10 ins. diam., bears S.21*E., 24 lks. dist.

Marked $\frac{1}{4}$ S 15 B T.

A fir, 12 ins. diam., bears N.24*W., 44 lks. dist.

Marked $\frac{1}{4}$ S 16 B T.

Ascend 250 ft. over SW. slope to

57.40 Spur, slopes NW.

Descend 360 ft. over NE. slope to

75.21 Squaw Creek, 50 lks. wide, course NW., ascend 30 ft. to

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 9, 10, 15 and 16, with brass cap marked

T30S | R1E
 S9 | S10
 S16 | S15
 1923

from which

A hemlock, 14 ins. diam., bears N.34*E., 84 lks. dist.

Marked T 30 S R 1 E S 10 B T.

A fir, 16 ins. diam., bears S.81*E., 11 lks. dist.

Marked T 30 S R 1 E S 15 B T.