

## County Surveyor's Record, Douglas County, Oregon

36

Subdivision of T. 30 S., R. 1 E.

CHAINS	
	<p>A fir, 28 ins. diam., bears S.41*W., 50 lks. dist.  Marked T 30 S R 1 E S 16 B T.</p> <p>A hemlock, 24 ins. diam., bears N.84*W., 53 lks. dist.  Marked T 30 S R 1 E S 9 B T.</p> <p>Land, mountainous.  Soil, clay loam, stony in places; second and third rate.  Timber, fir, hemlock, cedar, and pine.  Undergrowth, chinquapin rhododendron, vine maple, and hazel.</p>
	<p>N.0*02'W., bet. secs. 9 and 10.  Over mountainous land, through scattered timber and dense undergrowth.  Ascend 100 ft. over SW. slope to</p>
8.25	Spur, slopes W., descend 175 ft. over NW. slope.
15.65	Left bank of South Fork of South Umpqua River, course SW.
16.31	Right bank of South Fork of South Umpqua River. Ascend 110 ft. over general SE. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\begin{array}{c} \frac{1}{4} \\ \text{S9} \mid \text{S10} \\ 1923 \end{array}$
	<p>from which</p> <p>A fir, 18 ins. diam., bears S.38*E., 33 lks. dist.  Marked <math>\frac{1}{4}</math> S 10 B T.</p> <p>A cedar, 18 ins. diam., bears S.14*W., 57 lks. dist.  Marked <math>\frac{1}{4}</math> S 9 B T.</p> <p>Ascend 200 ft. over SE. slope.</p>
46.25	Spur, slopes SE., descend 80 ft.
50.25	Enter fir thicket, bears E. and W.
62.00	Draw, opens SE., ascend 80 ft.
68.12	Leave fir thicket, enter pine openings, bears NW. and SE.
79.00	Leave pine openings, enter heavy timber, bears NW. and SE.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 3, 4, 9 and 10, with brass cap marked