

## County Surveyor's Record, Douglas County, Oregon

37

Subdivision of T. 30 S., R. 1 E.

CHAINS

T30S	R1E
S4	S3
S9	S10
1923	

from which

A pine, 30 ins. diam., bears N.7\*E., 24 lks. dist.

Marked T 30 S R 1 E S 3 B T.

A cedar, 20 ins. diam., bears S.30\*E., 39 lks. dist.

Marked T 30 S R 1 E S 10 B T.

A pine, 28 ins. diam., bears S.57\*W., 59 lks. dist.

Marked T 30 S R 1 E S 9 B T.

A fir, 30 ins. diam., bears N.19\*W., 72 lks. dist.

Marked T 30 S R 1 E S 4 B T.

Land, mountainous.

Soil, clay loam, second rate.

Timber, fir, pine, and cedar.

Undergrowth, chinquapin, laurel, hemlock, hazel and fir.

N.0\*02\*W., on a true line bet. secs. 3 and 4.

Over mountainous land, through medium heavy timber and dense undergrowth.

Descend 100 ft. over NE. slope to

8.75 Draw, opens SE., ascent 90 ft. to

15.00 Spur, slopes E., descend 175 ft. over NE. slope.

23.75 Creek, 5 lks. wide, course SE.

Ascend 210 ft. over SW. slope to

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked

$\frac{1}{4}$	
S4	S3
1923	

from which

A fir, 10 ins. diam., bears N.78\*E., 7 lks. dist.

Marked  $\frac{1}{4}$  S 3 B T.

A fir, 10 ins. diam., bears S.57\*W., 5 lks. dist.

Marked  $\frac{1}{4}$  S 4 B T.