

## County Surveyor's Record, Douglas County, Oregon

47

## Subdivision of T. 30 S., R. 1 E.

CHAINS	
	A fir, 20 ins. diam., bears N.43*W., 45 lks. dist. Marked $\frac{1}{4}$ S 21 B T.
	A fir, 12 ins. diam., bears S.23*W., 27 lks. dist. Marked $\frac{1}{4}$ S 28 B T.
	Ascend over SE. slope.
41.68	Dry ravine, course NE., living water below line.
47.57	Low spur, slopes NE. Ascend over NE. slope to
73.00	Spur, slopes NW., 450 ft. above $\frac{1}{4}$ sec. cor. Descend 170 ft. to sec. cor., over NW. slope.
79.62	Old Biellac Burn Trail, bears N. and S.
79.92	The cor. of secs. 20, 21, 28 and 29. Land, mountainous. Soil, clay loam, stony in places, second and third rate. Timber, fir, hemlock, cedar, and pine. Undergrowth, fir, hazel, vine maple, chinquapin and laurel.
	N.0*03*W., bet. secs. 20 and 21. Over mountainous land, through medium dense small timber and dense undergrowth, in old burn. Over rolling land near top of spur, general W. slope.
0.40	Old Biellac Burn Trail, bears NW. and SE.
2.39	Same trail, bears NE. and SW.
6.82	Same trail, bears NW. and SE. Enter pine glades, bears NW. and SE.
9.57	Same trail, bears NE. and SW.
11.85	Same trail, bears NW. and SE.
15.97	Leave pine glades, bears NW. and SE. Ascend gradually over NE. slope.
26.00	Spur, slopes NW. Enter heavy timber, bears NW. and SE. Descend gradually over NE. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked $\frac{1}{4}$ S20 S21 1923