

County Surveyor's Record, Douglas County, Oregon

47

Subdivision of T. 30 S., R. 1 E.

CHAINS	<p>N.0°03'W., bet. secs. 8 and 9.</p> <p>Over mountainous land, through small and scattering old timber and dense undergrowth.</p> <p>Ascend 150 ft. over SE. slope to</p> <p>15.70 Spur, slopes SW., ascend 225 ft. over SW. slope.</p> <p>38.75 Spur, slopes W., descend gradually over NW. slope.</p> <p>40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, for <math>\frac{1}{4}</math> sec. cor., with brass cap marked</p> <div style="text-align: center; margin: 10px 0;"> <math display="block">\begin{array}{c} \frac{1}{4} \\ \text{S8}   \text{S9} \\ 1923 \end{array}</math> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 30 ins. diam., bears N.22°E., 16 lks. dist. Marked <math>\frac{1}{4}</math> S 9 B T.</p> <p style="padding-left: 40px;">A fir, 30 ins. diam., bears S.19°W., 72 lks. dist. Marked <math>\frac{1}{4}</math> S 8 B T.</p> <p>Descend 90 ft. over NW. slope.</p> <p>50.00 Foot of descent. Draw, opens W.</p> <p>Ascend gradually over SW. slope.</p> <p>60.18 Trail, bears E. and W.</p> <p>72.00 Top of spur, slopes W., descend 160 ft. over NW. slope.</p> <p>80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in ground, for cor. of secs. 4, 5, 8 and 9, with brass cap marked</p> <div style="text-align: center; margin: 10px 0;"> <math display="block">\begin{array}{c} \text{T30S R1E} \\ \hline \text{S5}   \text{S4} \\ \hline \text{S8}   \text{S9} \\ 1923 \end{array}</math> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears N.72°E., 17 lks. dist. Marked T30 S R 1 E S 4 B T.</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears S.83°E., 24 lks. dist. Marked T 30 S R 1 E S 9 B T.</p> <p style="padding-left: 40px;">A fir, 24 ins. diam., bears S.62°W., 40 lks. dist. Marked T 30 S R 1 E S 8 B T.</p> <p style="padding-left: 40px;">A fir, 28 ins. diam., bears N.57°W., 22 lks. dist. Marked T 30 S R 1 E S 5 B T.</p>
--------	--