

County Surveyor's Record, Douglas County, Oregon

50

Subdivision of T. 30 S., R. 1 E.

CHAINS	
	From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., hereinbefore described.
	N.0*04'W., bet. secs. 31 and 32.
	Over mountainous land, through old burn and dense undergrowth.
	Ascend 300 ft. over S. slope to divide.
8.90	Enter green timber, bears E. and W.
10.63	Trail, bears E. and W.
19.92	Old Beaver Lake Trail, bears NW. and SE.
25.00	Low Spur, slopes SW.
35.00	Divide bet. Beaver Creek and South Fork of South Umpqua River, bears NW. and SE.
	Descend gradually to
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4}$ S31 S32 1923
	from which
	A cedar, 24 ins. diam., bears S.7*E., 20 lks. dist.
	Marked $\frac{1}{4}$ S 32 B T.
	A fir, 10 ins. diam., bears S.14*W., 42 lks. dist.
	Marked $\frac{1}{4}$ S 31 B T.
	Descend 460 ft. over broken NE. slope.
55.77	Brook, 1 lk. wide, course NE.
69.22	Brook, 3 lks. wide, course NE.
78.33	Brook, 1 lk. wide, course NE.
79.54	Brook, 1 lk. wide, course NE.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in ground, for cor. of secs. 29, 30, 31 and 32, with brass cap marked
	T30S R1E S30 S29 S31 S32 1923
	from which