

County Surveyor's Record, Douglas County, Oregon

52

Subdivision of T. 30 S., R. 1 E.

CHAINS	
	<p>A fir, 38 ins. diam., bears S.27*W., 37 lks. dist. . Marked $\frac{1}{4}$ S 32 B T.</p> <p>Ascend 300 ft. over SE. slope to</p>
57.00	Spur, slopes N., descend 160 ft. over NW. slope to
66.75	Draw, opens N. ascend 40 ft. to
71.75	Spur, slopes N., descend 60 ft. to
76.05	Brook, 2 lks. wide, course NE., ascend 60 ft. over NE. slope to
80.00	The cor. of secs. 29, 30, 31 and 32. Land, mountainous. Soil, stony clay loam, 2nd. and 3rd. rate. Timber, fir, hemlock, pine, and cedar. Undergrowth, laurel, chinquapin, hazel, and vine maple.
	<p>West, on a random line bet. secs. 30 and 31.</p>
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.34	Intersect Willamette Meridian, 12 lks. N. of the cor. of secs. 30 and 31 only, hereinbefore described. Thence N.89*55'E., on a true line, bet. secs. 30 and 31 Over mountainous land, through heavy timber and dense undergrowth. Ascend 390 ft. over SW. slope to.
15.80	Divide, between Beaver Creek and the South Fork of the South Umpqua River, bears NW. and SE. Descend 300 ft. over broken NE. slope to $\frac{1}{4}$ sec. cor.
25.98	Trail, bears NW. and SE.
29.64	Trail, bears NE. and SW.
31.14	Green Prairie Spring, bears N. 1 ch. dist., flows NE.
40.34	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked
	<p>S30 $\frac{1}{4}$ ——— S31 1923</p>
	from which