

County Surveyor's Record, Douglas County, Oregon

11025

Dependent Resurvey of the SOUTH Boundary,
Independent Resurvey of the WEST Boundary, and Survey of
EAST Boundary, and Subdivision of Township 30 South, Range 3 E.,
Executed by Herbert N. Raymond, U. S. Cadastral Engineer under
Special Instructions dated Dec. 27, 1920 and Sept. 9, 1927.

CHAINS

Township 30 South, Range 3 East.
Retracement of SOUTH Boundary.

From the corner of Ts. 30 and 31 S., Rs. 3 and 4 E.
S.89°30'W., retracing bet. Secs. 1 and 36.

40.26 Fall 27 lks. S. of $\frac{1}{4}$ Sec. cor.

From $\frac{1}{4}$ sec. cor. S.89°30'W.

40.30 Fall 5 lks. S. of the cor. of Secs. 1, 2, 35 and 36.

The bearing and length of the E. half mile is S.89°53'W.,
40.26 chs. and the W. half is S.89°34'W., 40.30 chs.

From the cor. of Secs. 1, 2, 35 and 36.

S.89°30'W., retracing bet. Secs. 2 and 35.

40.30 Fall 2 lks. N. of $\frac{1}{4}$ sec. cor.

From $\frac{1}{4}$ sec. cor. S.89°30'W.

40.32 Fall 38 lks. N. of the cor. of Secs. 2, 3, 34 and 35.

The bearing and length of the E. half mile is S.89°28'W.,
40.30 chs. and the W. half is S.88°58'W., 40.33 chs.

From the cor. of Secs. 2, 3, 34 and 35.

South, 2.90 chs.

West, 3.00 "

N.86°W., 6.60 "

N.56°W., 3.70 "

West, 27.58 " to $\frac{1}{4}$ sec. cor.

From $\frac{1}{4}$ sec. cor. S.89°30'W.

10.50 Offset South, 5.00 chs.; thence S.89°30'W., 21.50 chs.

32.00 Offset North, 5.00 chs.; thence S.89°30'W., 7.82 chs.

39.82 The cor. of Secs. 3, 4, 33 and 34.

The bearing and length of the E. half mile is S.89°28'W.,
40.23 chs. and the W. half is S.89°30'W., 39.82 chs.

From the cor. of Secs. 3, 4, 33 and 34.

S.89°30'W., retracing bet. Secs. 4 and 33.