

County Surveyor's Record, Douglas County, Oregon

Township 30 South, Range 3 East.
Retracement of SOUTH Boundary.

CHAINS

- 39.77 Fall 5 lks. N. of $\frac{1}{4}$ sec. cor.
From $\frac{1}{4}$ sec. cor. S.89°30'W.
- 39.27 Fall 6 lks. N. of the cor. of Secs. 4, 5, 32 and 33.
The bearing and length of the E. half mile is S.89°26'W.,
39.77 chs. and the W. half is S.89°25'W., 39.27 chs.
-
- From the cor. of Secs. 4, 5, 32 and 33.
S.89°30'W., retracing bet. Secs. 5 and 32.
- 40.12 Fall 5 lks. S. of $\frac{1}{4}$ sec. cor.
From $\frac{1}{4}$ sec. cor. S.89°30'W.
- 40.02 Fall 48 lks. N. of the cor. of Secs. 5, 6, 31 and 32.
The bearing and length of the E. half mile is S.89°34'W.,
40.12 chs. and the W. half is S.88°49'W., 40.03 chs.
-
- From the cor. of Secs. 5, 6, 31 and 32.
S.89°30'W., retracing bet. Secs. 6 and 31.
- 40.56 Fall 16 lks. N. of $\frac{1}{4}$ sec. cor.
From $\frac{1}{4}$ sec. cor. S.89°30'W.
- 45.40 Intersect W. bdy. of the Tp. at the cor. of Ts. 30 and
31 S., Rs. 2 and 3 E.
The bearing and length of the E. half mile is S.89°16'W.,
40.56 chs. and the W. half is S.89°30'W., 45.40 chs.

Note: The retracement of the South Boundary of T. 30 S.,
R.3 E., developed the fact that Mrs. Fred Mensch, U.S.
Cadastral Engineer, in surveying the line between Ts.
30 S., Rs. 2 and 3 E., under Group No. 62, in 1923,
initiated his survey from a spurious or unofficial
corner of Ts. 30 and 31 S., Rs. 2 and 3 E., from
which the recorded official corner bears N.7°59'E.,