

County Surveyor's Record, Douglas County, Oregon

Township 30 South, Range 3 East,
Resurvey of South Boundary.

CHAINS

A Red Fir, (orig.) 60 ins. diam., bears S.80*W.,

33 lks. dist., mkd. T 31 S R 3 E S 1 B T.

A White Fir, (orig.)/16^{dead,} ins. diam., bears N.60*W.,
42 lks. dist., with traces of original marking.

A White Fir, (new) 14 ins. diam., bears N.15 $\frac{1}{2}$ *W.,

56 lks. dist., marked T 30 S R 3 E S 36 B T.

S.89*53*W., bet. Secs. 1 and 36.

Over nearly level land, through scattering timber and
medium undergrowth.

5.50 Descend 110 ft. over NW. slope.

13.50 Draw, drains SW; ascend 125 ft. over SE. slope.

19.25 Top of ascent; thence over rolling land.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in
the ground, for $\frac{1}{4}$ Sec. cor. of Sec. 36 only, with
brass cap marked

$\frac{1}{4}$ S 36
1927

from which

A Pine, 14 ins. diam., bears N.76*E., 120 lks.
dist., marked $\frac{1}{4}$ S 36 B T.

A Pine, 10 ins. diam., bears N.31*W., 61 lks.
dist., marked $\frac{1}{4}$ S 36 B T.

40.26 The $\frac{1}{4}$ Sec. cor. established for Secs. 1 and 36, the
position of which is determined by reference to the
original bearing trees. At this point
Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in
the ground, for $\frac{1}{4}$ Sec. cor. of Sec. 1 only, with
brass cap marked

$\frac{1}{4}$ S 1
1927

from which

A Pine, (orig.) 9 ins. diam., bears S.45 $\frac{1}{2}$ *E.,
35 lks. dist., marked $\frac{1}{4}$ S 1 B T.

A Pine, (new) 10 ins. diam., bears S.45 $\frac{1}{2}$ *W.,
72 lks. dist., marked $\frac{1}{4}$ S 1 B T.

A pine, (orig) 9 ins. diam., bears N.41*W.,
7 lks. dist., marked $\frac{1}{4}$ S B T. Obliterated.