

Township 30 South, Range 3 East.
Resurvey of South Boundary.

CHAINS

Thence

S.89°34'W.

39.74 Point 80.00 chs. in Westing from SE. cor. of Tp.

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, for cor. of Secs. 35 and 36 only, with brass cap mkd.

T 30 S	R 3 E
S 35	S 36
T 31 S	R 3 E
S 1	
1927	

from which

A Fir, 8 ins. diam., bears N.50½°E., 55 lks. dist., mkd. T 30 S R 3 E S 36 B T.

A Fir, 12 ins. diam., bears N.31°W., 80 lks. dist., mkd. T 30 S R 3 E S 35 B T.

Thence bet. Secs. 1 and 35.

40.30 The cor. established for Secs. 1, 2, 35 and 36, which is an unmarked pumice stone, 10x10x8 ins., loosely set. In place of which

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, for cor. of Secs. 1 and 2 only, with brass cap mkd.

T 30 S	R 3 E
S 35	
S 2	S 1
T 31 S	R 3 E
1927	

from which

A Red Fir, (orig.) 40 ins. diam., bears N.61°E., 18 lks. dist., mkd. T 30 S R 3 E S 36 B T.

A White Fir, (orig.) 12 ins. diam., bears S.19°E., 29 lks. dist., mkd. T 31 S R 3 E S 1 B T.

A White Fir, (orig.) 12 ins. diam., bears S.78°W., 28 lks. dist., mkd. T 31 S R 3 E S 2 B T.

A Red Fir, (orig.) 20 ins. diam., bears N.35°W., 29 lks. dist., mkd. T 30 S R 3 E S 35 B T.

Obliterate marking on bearing Trees N. of line.
Land, level and rolling.
Soil, sandy, 2nd rate.
Timber, Fir, Pine and Cedar.