

Township 30 South, Range 3 East.
 Resurvey of South Boundary.

CHAINS

34.60 Leave Highway; desc. 10 ft. over NW. slope.
 36.70 A Channel of part of the Rogue River, 25 lks. wide,
 course SW.; asc. 10 ft. over SE. slope to
 39.15 Point 80.00 chs. in Westing from SE. cor. of Sec. 35.
 Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in
 the ground, for cor. of Secs. 34 and 35 only, with
 brass cap mkd.

T 30 S | R 3 E
 S 34 | S 35
 T 31 S R 3 E
 S 2
 1928

from which

A Pine, 22 ins. diam., bears N.62*E., 27 lks.
 dist., mkd. T 30 S R 3 E S 35 B T.

A Pine, 24 ins. diam., bears N.15*W., 48 lks.
 dist., mkd. T 30 S R 3 E S 34 B T.

Thence bet. Secs. 2 and 34.

Desc. 5 ft. over NW. slope to

40.33 The cor. established for Secs. 2, 3, 34 and 35, which
 is a cross (X) cut on a projecting point of lava
 bed rock, 2x2x2 ft.; I cut 2 grooves E., 4 grooves
 W., S 2 SE., S 3 SW. of the cross; from which
 the original bearing trees

A Red Fir, 24 ins. diam., bears N.32*E., 127 lks.
 dist., mkd. T 30 S R 3 E S 35 B T.

A Red Fir, 20 ins. diam., bears S.30*E., 25 lks.
 dist., mkd. T 31 S R 3 E S 2 B T.

A Pine, 15 ins. diam., bears S.32*W., 33 lks.
 dist., mkd. T 31 S R 3 E S 3 B T.

A Pine, 12 ins. diam., bears N.4*W., 67 lks.
 dist., mkd. T 30 S R 3 E S 34 B T.

Obliterate marking on bearing trees N. of line.

This corner will hereafter refer to Secs. 2 and 3 only.

Land, level and rolling.