


County Surveyor's Record, Douglas County, Oregon

Township 30 South, Range 3 East.
Resurvey of South Boundary.

CHAINS

the ground, for cor. of Secs. 3 and 4 only, with
brass cap mkd.



from which

- A Hemlock, (orig.) 18 ins. diam., bears N.16°E.,
110 lks. dist., mkd. T 30 S R 3 E S 34 B T.
- A Hemlock, (orig.) 28 ins. diam., bears S.45°E.,
28 lks. dist., mkd. T 31 S R 3 E S 3 B T.
- A Hemlock, (orig.) 18 ins. diam., bears S.30°W.,
38 lks. dist., mkd. T 31 S R 3 E S 4 B T.
- A Hemlock, (orig.) 16 ins. diam., bears N.13°W.,
95 lks. dist., mkd. T 30 S R 3 E S 33 B T.

Obliterate marking on bearing trees N. of line.
 Land, level, rolling, and mountainous.
 Soil, sandy and rocky, 2nd and 4th rate.
 Timber, Fir, Pine and Hemlock.
 Undergrowth, Hazel, Yew and Willow.

S.89°26'W., bet. Secs. 4 and 33.

Over level land, through medium timber and medium under-
growth.

- 4.40 Left bank of Rogue River, 2.00 chs. wide, course SW.
- 6.85 Right bank of river; thence over rolling land.
- 11.40 Asc. 275 ft. over E. slope to 1/4 sec. cor.
- 38.77 Point 40.00 chs. in Westing from SE. cor. of Sec. 33.
Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in
the ground, to bed rock, and build a mound of stone,
2 ft. base, 9 ins. high, around the post, for 1/4 sec.
cor. of Sec. 33 only, with brass cap mkd.