

Township 30 South, Range 3 East.
Resurvey of South Boundary.

CHAINS

$\frac{1}{4}$ S 33

1928

From which

A Fir, 20 ins. diam., bears N.48*W., 67 lks.
dist., mkd. $\frac{1}{4}$ S 33 B T.

A Fir, 6 ins. diam., bears N.33*W., 22 lks.
dist., mkd. $\frac{1}{4}$ S 33 B T.

39.77 The $\frac{1}{4}$ sec. cor. established for Secs. 4 and 33, which is a country rock, 12x8x8 ins. loosely set, marked and witnessed as described in the Field Notes of the original survey. In place of the stone, Set an iron post, 3 ft. long, 1 ins. diam., 30 ins. in the ground, for $\frac{1}{4}$ sec. cor. of Sec. 4 only, with brass cap mkd.

$\frac{1}{4}$ S 4
1928

from which

A Fir, (orig.) 30 ins. diam., bears S.60*E., 21 lks.
dist., mkd. $\frac{1}{4}$ S 4 B T.

A Fir, (new) 11 ins. diam., bears S.77*W., 19 lks.
dist., mkd. $\frac{1}{4}$ S 4 B T.

A Fir, (orig.) 22 ins. diam., bears N.45*W., 23 lks.
dist., mkd. $\frac{1}{4}$ S B T. Obliterated.

Thence

S.89*25'W.

Asc. 790 ft. over E. slope.

26.35 Ridge, bears N. and S.; desc. 390 ft. over NW. slope to

39.00 Point 80.00 chs. in Westing from SE. cor. of Sec. 33.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of Secs. 32 and 33 only, with brass cap mkd.