

County Surveyor's Record, Douglas County, Oregon

Township 30 South, Range 3 East.
Resurvey of South Boundary.

CHAINS

Thence

S.88°49'W.

Desc. 50 ft. over W. slope.

5.65 Creek, 8 lks. wide, Course S.; asc. 510 ft. over E. slope to

39.62 Point 80.00 chs. in Westing from SE. cor. of Sec. 32. Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the ground, to bed rock, and build a mound of stone, 4 ft. base, 2 ft. high, around the post, for cor. of Secs. 31 and 32 only, with brass cap mkd.

T 30 S | R 3 E
S 31 | S 32

T 31 S R 3 E
S 5
1928

from which

A Fir, 26 ins. diam., bears N.87°W., 99 lks. dist., mkd. T 30 S R 3 E S 31 B T.

No tree available in Sec. 32 because of cliffs.

Thence bet. Secs. 5 and 31.

40.03 The cor. established for Secs. 5, 6, 31 and 32, which is a cross (x) cut on soft surface rock, witnessed approximately as described in the Field Notes of the original survey. In place of the cross, Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. deep to hard rock, and build a mound of stone, 3 ft. base, 1½ ft. high around the post, for cor. of Secs. 5 and 6 only, with brass cap mkd.

T 30 S R 3 E
S 31

S 6 | S 5
T 31 S R 3 E
1928

from which