

Township 30 South, Range 3 East.
Resurvey of South Boundary.

CHAINS

from which

A Cedar, 16 ins. diam., bears N.11*E., 24 lks.
dist., mkd. $\frac{1}{4}$ S 31 B T.

A Cedar, 14 ins. diam., bears N.23*W., 32 lks.
dist., mkd. $\frac{1}{4}$ S 31 B T.

40.56 The $\frac{1}{4}$ sec. cor. established for Secs. 6 and 31, which
is a country rock, 14x8x8 ins. loosely set and marked
 $\frac{1}{4}$ on N. face.

Against the N. side of the stone

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in
the ground, for $\frac{1}{4}$ sec. cor. of Sec. 6 only, with
brass cap mkd.

$\frac{1}{4}$ S 6
1928

from which

A Cedar, (orig.) 12 ins. dia., bears S.20*E.,
22 lks. dist., mkd. $\frac{1}{4}$ S 6 B T.

A Fir, (new) 22 ins. dia., bears S.69*W.,
32 lks. dist., mkd. $\frac{1}{4}$ S 6 B T.

A Cedar, (orig.) 12 ins. dia., bears N.14*W.,
43 lks. dist., mkd. $\frac{1}{4}$ S 31 B T.

Obliterate markings on the bearing tree N. of line,

Thence

S.89*30'W.

Desc. slightly over W. slope.

1.04 Wash, 5 lks. wide, Course S.; asc. 120 ft. over SE.
slope.

13.50 Spur, slopes SW.; desc. 345 ft. over W. slope.

34.72 Spring branch, 2 lks. wide, course S.; asc. 185 ft.
over SE. slope to cor.; enter heavy timber, bears
N. and S.

45.40 The cor. of Ts. 30 and 31 S., Rs 2 and 3 E., the
position of which is determined by reference to the