

18
County Surveyor's Record, Douglas County, Oregon

Township 30 South, Range 3 East.
Resurvey of West Boundary.

CHAINS

- 40.00 Set an iron post, 3 ft. long, 1 in. dia., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. of Sec. 36 only, with brass cap mkd.
- S 36 $\frac{1}{4}$
1928
- from which
- A Chinquapin, 4 ins. dia., bears S.73*W., 31 lks. dist., mkd. $\frac{1}{4}$ S 36 B T.
- A Pine, 54 ins. dia., bears N.72*W., 9 lks. dist., mkd. $\frac{1}{4}$ S 36 B T.
- Obliterate old $\frac{1}{4}$ sec. cor. without taking a tie to it.
- 43.87 Point 40.00 chs. in Southing from NW. cor. of Sec. 31, determined as hereinafter described.
- Set an iron post, 3 ft. long, 1 in. dia., 30 ins. in the ground, for $\frac{1}{4}$ sec. cor. of Sec. 31 only, with brass cap mkd.
- $\frac{1}{4}$
S 31
1928
- from which
- A Pine, 5 ins. dia., bears N.19*E., 19 lks. dist., mkd. $\frac{1}{4}$ S 31 B T.
- A Pine, 7 ins. dia., bears S.17*E., 37 lks. dist., mkd. $\frac{1}{4}$ S 31 B T.
- Desc. 65 ft. over NW. slope.
- 47.80 Wash, 3 lks. wide, Course W.; thence over W. slope.
- 65.65 Creek, 5 lks. wide, Course W.; asc. 305 ft. over SE. slope to C C.
- 75.04 The cor. established for Secs. 25, 30, 31 and 36, bears West, 32 lks. dist. We obliterate this corner.
- 77.00 Enter dense undergrowth.
- 80.00 Set an iron post, 3 ft. long, 2 ins. dia., 27 ins. in the ground, for cor. of Secs. 25 and 36 only, with brass cap mkd.