

20
County Surveyor's Record, Douglas County, Oregon

Township 30 South, Range 3 East.
Resurvey of West Boundary.

CHAINS

N.0°13'E., bet. Secs. 25 and 30.

Over mountainous land, through heavy timber and dense undergrowth.

Asc. 315 ft. over SE. slope.

21.00 Spur, slopes SW.; desc. 390 ft. over NW. slope.

32.30 Creek, 3 lks. wide, Course W.; asc. 210 ft. over S. slope to $\frac{1}{4}$ sec. cor. of Sec. 30.

36.13 Point 40.00 chs. in Northing from cor. of Secs. 25 and 36 only.

Set an iron post, 3 ft. long, 1 in. dia., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor. of Sec. 25 only, with brass cap mkd.

$\frac{1}{4}$
|
S 25
|
1928

from which

A Fir, 30 ins. dia., bears N.25°W., 68 lks. dist., mkd. $\frac{1}{4}$ S 25 B T.

A Fir, 30 ins. dia., bears S.8°W., 73 lks. dist., mkd. $\frac{1}{4}$ S 25 B T.

Obliterate old $\frac{1}{4}$ sec. cor., without taking a tie to it.

39.95 Mid-point bet. NW. and SW. cors. of Sec. 30, determined as hereinafter described.

Set an iron post, 3 ft. long, 1 in. dia., 30 ins. in the ground, for $\frac{1}{4}$ sec. cor. of Sec. 25 only, with brass cap mkd.

$\frac{1}{4}$
|
S 30
|
1928

from which

A Fir, 5 ins. dia., bears N.71°E., 12 lks. dist., mkd. $\frac{1}{4}$ S 30 B T.

A Fir, 6 ins. dia., bears S.12°E., 27 lks. dist.,