

Township 30 South, Range 3 East.
Resurvey of West Boundary.

CHAINS

dist., mkd. $\frac{1}{4}$ S 24 B T.

A fir, 18 ins. dia., bears N. $6\frac{1}{2}^{\circ}$ W., 74 lks.

dist., mkd. $\frac{1}{4}$ S-24 B T.

Obliterate old $\frac{1}{4}$ sec. cor., without taking a tie to it.

39.87 Spring branch, 1 lks. wide, course SW.

40.12 Mid-point bet. NW. and SW. cors. of sec. 19.

Set an iron post, 3 ft. long, 1 in. dia., 18 ins. in the ground, to bed rock; and build a mound of stone, 2 ft. base, 1 ft. high around the post, for $\frac{1}{4}$ sec. cor. of sec. 19 only, with brass cap mkd.

| $\frac{1}{4}$
| S 19
1928

from which

A fir, 7 ins. dia., bears N. $4\frac{1}{2}^{\circ}$ E., 43 lks.

dist., mkd. $\frac{1}{4}$ S 19 B T.

A fir, 6 ins. dia., bears S. 70° E., 7 lks.

dist., mkd. $\frac{1}{4}$ S 19 B T.

Asc. 845 ft. over broken SW. slope.

55. 30 Forest Service Trail, bears NW. and SE.

70.53 The cor. established for secs. 13, 18, 19 and 24, bears West, 24 lks. dist. We obliterate this cor.

75.50 Enter dense 2nd growth, bears NW and SE.

76.23 Point 80.00 chs. in northing from cor. of secs. 24 and 25 only.

Set an iron post, 3 ft. long, 2 ins. dia., 32 ins. in the ground, for cor. of secs. 13 and 24 only, with brass cap mkd.

T 30 S |
-S 13 | T 30 S
S 24 | R 3 E
R 2 E | S 19
1928

from which

A fir, 42 ins. dia., bears S. $19\frac{1}{2}^{\circ}$ W. 79 lks.

dist., mkd. T 30 S R 2 E S 24 B T.

A fir, 34 ins. dia., bears N. 66° W., 96 lks.