

County Surveyor's Record, Douglas County, Oregon

Township 30 South, Range 3 East.
Resurvey of West Boundary.

CHAINS

dist., mkd. T 30 S R 2 E S 13 B T.

Thence bet. secs. 13 and 19,

78.00 Spur, slopes W.; desc. 20 ft. over NW. slope to

80.24 Point of intersection of the line bet. secs. 18 and 19,
determined as hereinafter described.

Set an iron post, 3 ft. long, 2 ins. dia., 18 ins. in
the ground, to bed rock with a mound of stone around
the post, for C C. of secs. 18 and 19, with brass cap
mkd.

```

      T 30 S
      |
T 30 S | S 18
      |  |
R 2 E |  | CC
      |  |
      | S 19
      |  |
      | R 3 E
      |  |
      | 1928
  
```

from which

A fir, 26 ins. dia., bears N.11°E., 55 lks.

dist., mkd. C C T 30 S R 3 E S 18 B T.

A larch, 34 ins. dia., bears S.19½°E., 183 lks.

dist., mkd. C C T 30 S R 3 E S 19 B T.

Land, mountainous.

Soil, sandy, gravelly, and rocky, 2nd rate.

Timber, fir, pine, and cedar.

Undergrowth, snow brush, hazel, huckleberry, small
fir, pine, and yew.

N. 0°13'E., bet. secs. 13 and 18.

Over mountainous land, through heavy timber and dense
undergrowth.

Desc. 530 ft. over NW. slope.

18.00 Leave dense undergrowth.

34.00 Spur, bears NW.; desc. 160 ft. over NE. slope to ¼ sec.
cor. of sec. 18; enter dense undergrowth.

35.99 Point 40.00 chs. in northing from SE. cor. of sec. 13.
Set an iron post, 3 ft. long, 1 ins. dia., 18 ins. in
the ground, to bed rock, and build a mound of stone,
3 ft. base, 1 ft. high, around the post, for ¼ sec.