

Township 30 South, Range 3 East.  
Resurvey of West Boundary.

CHAINS

- 5.75 A rocky spur, bears E.; desc. 325 ft. over broken NE. slope, leave burn, enter heavy timber, bears E. and W.
- 23.40 Draw, course E.; asc. 45 ft. over SE. slope.
- 27.50 Spur, bears E.; desc. 90 ft. over NE. slope to  $\frac{1}{4}$  sec. cor. of sec. 7.
- 35.97 Point 40.00 chs. in northing from the cor. of secs. 12 and 13 only.  
Set an iron post, 3 ft. long, 1 in. dia., 30 ins. in the ground, for  $\frac{1}{4}$  sec. cor. of sec. 12 only, with brass cap mkd.
- $\frac{1}{4}$   
S 12  
1928
- from which
- A fir, 4 ins. dia., bears N.69\*W., 18 lks.  
dist., mkd.  $\frac{1}{4}$  S 12 B T.
- A Pine, 8 ins. dia., bears N.24\*W., 35 lks.  
dist., mkd.  $\frac{1}{4}$  S 12 B T.
- Obliterate old  $\frac{1}{4}$  sec. cor., without taking a tie to it.
- 39.86 Mid-point bet. NW. and SW. cors. of sec. 7, determined as hereinafter described.  
Set an iron post, 3 ft. long, 1 in. dia., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor. of sec. 7 only, with brass cap mkd.
- $\frac{1}{4}$   
S 7  
1928
- from which
- A fir, 36 ins. dia. bears N.22\*E., 80 lks.  
dist., mkd.  $\frac{1}{4}$  S 7 B T.
- A fir, 4 ins. dia., bears N.86\*W., 37 lks.  
dist., mkd.  $\frac{1}{4}$  S 7 B T.
- 40.25 Spur, slopes NE.; desc. 960 ft. over broken NE. slope.
- 69.48 The cor. established for secs. 1, 6, 7, and 12. bears East, 2 lks. dist. We obliterate this cor.
- 69.90 Middle of Falcon Creek, 35 lks. wide, course W.; asc.