

County Surveyor's Record, Douglas County, Oregon

Township 30 South, Range 3 East.
Resurvey of West Boundary.

CHAINS

200 ft. over S. slope to C C.

75.97 Point 80.00 chs. in northing from the cor. of secs. 12 and 13 only.

Set an iron post, 3 ft. long, 2 ins. dia., 30 ins. in the ground, for cor. of secs. 1 and 12 only, with brass cap mkd.

T 30 S		T 30 S
S 1		R 3 E
S 12		S 7
R 2 E		
		1928

from which

A cedar, 18 ins. dia., bears S.66*W., 66 lks. dist., mkd. T 30 S R 2 E S 12 B T.

A fir, 10 ins. dia., bears N.63*W 29 lks. dist., mkd. T 30 S R 2 E S 1 B T.

Thence bet. secs. 1 and 7.

79.72 Point of intersection of the line bet. secs. 6 and 7, determined as hereinafter described.

Set an iron post, 3 ft. long, 2 ins. dia., 30 ins. in the ground, for closing cor. of secs. 6 and 7, with brass cap mkd.

T 30 S		T 30 S
R 2 E		S 6
S 1		S 7
		R 3 E
		CC
		1928

from which

A fir, 15 ins. dia., bears N.25*E., 27 lks. dist., mkd. C C T 30 S R 3 E S 6 B T.

A fir, 45 ins. dia., bears S.68*E., 62 lks. dist., mkd. C C T 30 S R 3 E S 7 B T.

Land, mountainous.

Soil, gravelly and rocky, 3rd rate.

Timber, fir, cedar, and pine,

Undergrowth, snow brush, vine maple, and hazel.