

40
County Surveyor's Record, Douglas County, Oregon

Township 30 South, Range 3 East.
Subdivision

CHAINS

- 16.50 Asc. 50 ft. over SE. slope.
- 25.00 Top of asc.; thence over nearly level land.
- 40.00 Set an iron post, 3 ft. long, 1 in. dia., 30 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
S 26/S 25
1928

from which

A pine, 34 ins. dia., bears S. 20*E., 35 lks. dist., mkd. $\frac{1}{4}$ S 25 B T.

A pine, 18 ins. dia., bears S. 18*W., 17 lks. dist., mkd. $\frac{1}{4}$ S 26 B T.

- 42.00 Desc. 70 ft. over NW. slope.
- 44.85 Middle of Bybee Creek, 25 lks. wide, course W.; asc. 75 ft. over S. slope.
- 50.75 Spur, slopes W.; desc. 75 ft. over NW. slope.
- 57.70 Foot of desc.; asc. 85 ft. over SW. slope to sec. cor.
- 71.12 Diamond Lake Road, bears NE. and SW.
- 74.66 Diamond Lake Road, bears NW. and SE.
- 80.00 Set an iron post, 3 ft. long, 2 ins. dia., 28 ins. in the ground, for cor. of secs. 23, 24, 25, and 26, with brass cap mkd.

T 30 S R 3 E
S 23/S 24
S 26/S 25
1928

from which

A pine, 7 ins. dia., bears N. 10 $\frac{1}{2}$ *E., 6 lks. dist., mkd. T 30 S R 3 E S 24 B T.

A fir, 18 ins. dia., bears S. 62 $\frac{1}{2}$ *E., 15 lks. dist., mkd. T 30 S R 3 E S 25 B T.

A fir, 8 ins. dia., bears S. 23 $\frac{1}{2}$ *W., 28 lks. dist., mkd. T 30 S R 3 E S 26 B T.

A pine, 16 ins. dia., bears N. 20*W., 48 lks. dist., mkd. T 30 S R 3 E S 23 B T.

Land, rolling and level.