

Township 30 South, Range 3 East.  
Subdivision.

CHAINS

dist., mkd. T 30 S R 3 E S 23 B T.

A fir, 18 ins. dia., bears N. 17°15'W., 178 lks.

dist., mkd. T 30 S R 3 E S 14 B T.

Land, rolling and level.

Soil, sandy and gravelly, 2nd rate.

Timber, pine, fir, and hemlock.

Undergrowth, snow brush, hazel, service, small pine  
and fir.

S.89°51'E., on a random line bet. secs. 13 and 24.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

79.96 Intersect E. bdy. of the Tp. 35 lks. S. of the cor.  
of secs. 13, 18, 19, and 24.

Thence

S.89°54'W., on a true line.

Over rolling land, through dense 2nd growth pine.

6.50 Diamond Lake Road, bears NE. and SW.

29.60 Desc. 195 ft. over SW. slope.

34.00 Foot of desc.; thence over river bottom, enter heavy  
timber, bears N. and S.

36.50 Left bank of the Rogue River, course S.

38.25 Right bank of the river, thence over level land subject.  
to overflow.

39.98 Point for  $\frac{1}{4}$  sec. cor. on unsafe ground.

42.50 Asc. a bank, 7 ft. high, bearing N. and S.

42.86 Set an iron post, 3 ft. long, 1 ins. dia., 30 ins. in  
the ground, for witness corner to  $\frac{1}{4}$  sec. cor., with  
brass cap mkd.

W C  
S 13  
 $\frac{1}{4}$   
S 24  
1928

from which

A pine, 16 ins. dia., bears N. 30 $\frac{1}{2}$ °E., 53 lks.

dist., mkd.  $\frac{1}{4}$  S 13 W C B T.