

Township 30 South, Range 3 East.

Subdivision.

CHAINS

fir, pine and hemlock.

---

N.0°01'W., bet. Secs. 11 and 12.

Over mountainous land, through scattering timber and  
dense undergrowth.

Asc. 300 ft. over broken SE. slope.

29.00 Spur, slopes E.; desc. 150 ft. over NE. slope to

40.00 Set an iron post, 3 ft. long, 1 in. dia., 18 ins. in  
the ground, to bed rock, and build a mound of stone,  
4 ft. base, 1 ft. high, around the post, for  $\frac{1}{4}$  sec.  
cor., with brass cap mkd.

$\frac{1}{4}$   
S 11 | S 12  
1928

from which

A Fir, 24 ins. dia., bears N.35 $\frac{1}{2}$ °E., 43 lks.  
dist., mkd.  $\frac{1}{4}$  S 12 B T.

A Fir, 36 ins. dia., bears N.24 $\frac{1}{2}$ °W., 68 lks.  
dist., mkd.  $\frac{1}{4}$  S 11 B T.

Desc. 70 ft. over NE. slope.

42.40 Creek, 4 lks. wide, Course E.; asc. 30 ft. over S. slope.

45.70 Spur, slopes E.; desc. 25 ft. over NE. slope.

48.45 Creek, 6 lks. wide, Course SE.; asc. 300 ft. over S.  
slope.

73.00 Spur, slopes SE., desc. slightly over E. slope to

80.00 Set an iron post, 3 ft. long, 2 ins. dia., 30 ins. in  
the ground, for cor. of Secs. 1, 2, 11 and 12, with  
brass cap mkd.

T 30 S R 3 E  
S 2 | S 1  
S 11 | S 12  
1928

from which

A Fir, 14 ins. dia., bears N.52°30'E., 42 lks.  
dist., mkd. T 30 S R 3 E S 1 B T.