

Township 30 South, Range 3 East.
Subdivision.

CHAINS

Asc. 40 ft. over SE. slope.

47.00 Draw, drains SE.; asc. 500 Ft. over S. slope.

62.50 Spur, slopes SW.; desc. 100 ft. over NW. slope.

73.20 Draw, drains SW.; asc. 15 ft. over W. slope. to

81.22 Intersect random sectional correction line 16 lks. E.

of temp. sec. cor. At point of intersection

Set an iron post, 3 ft. long, 2 ins. dia., 20 ins. in

the ground, to bed rock, and build a mound of stone,

3 ft. base, 1 ft. high, around the post, for cor. of

secs. 26, 27, 34, and 35, with brass cap mkd.

T	30	S	R	3	E
	S	27		S	26
	S	34		S	35
	1928				

from which

A fir, 10 ins. dia., bears N. $83\frac{1}{2}^{\circ}$ E. 234 lks.

dist., mkd. T 30 S R 3 E S 26 B T.

A fir, 8 ins. dia., bears S. $21\frac{1}{2}^{\circ}$ E., 163 lks.

dist., mkd. T 30 S R 3 E S 35 B T.

A fir, 18 ins. dia., bears S. $57\frac{1}{2}^{\circ}$ W., 112 lks.

dist., mkd. T 30 S R 3 E S 34 B T.

A fir, 36 ins. dia., bears N. $60\frac{1}{2}^{\circ}$ W., 119 lks.

dist., mkd. T 30 S R 3 E S 27 B T.

Land, rolling and mountainous.

Soil, sandy, gravelly, and rocky, 3rd rate.

Timber, fir, pine, hemlock, and cedar.

Undergrowth, willow, alder, snow brush, small fir
and pine.

From the cor. of secs. 25, 26, 35, and 36.

West, on a true sectional correction line, bet. secs.
26 and 35.

Over rolling land, through scattering timber and dense
undergrowth.

Asc. 20 ft. over SE. slope.