

County Surveyor's Record, ⁵²Douglas County, Oregon

Township 30 South, Range 3 East.
Subdivision.

CHAINS

1.68 Diamond Lake Road, bears NE. and SW.
3.00 Top of ase. on low ridge, which bears NE. and SW.; desc. slightly over N. slope to
21.40 Desc. 100 ft. over broken NW. slope.
26.85 Left bank of the Rogue River, course SW.
28.95 Right bank of the river; asc. 240 ft. over SE. slope to
39.94 Set an iron post, 3 ft. long, 1 in. dia., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

S 26
 $\frac{1}{4}$
S 35
1928

from which

A fir, 20 ins. dia., bears S.49*E., 38 lks.
dist., mkd. $\frac{1}{4}$ S 35 B T.

A fir, 14 ins. dia., bears N.42*W., 35 lks.
dist., mkd. $\frac{1}{2}$ S 26 B T.

Asc. 210 ft. over SE. slope.
55.00 Rock spur, slopes SE.; desc. 25 ft. over SW slope.
59.00 Draw, drains S.; asc. 330 ft. over E. slope.
77.40 Spur ridge, bears NE. and SW.; desc. 70 ft. over W. slope to
79.88 The cor. of secs. 26, 27, 34, and 35.
Land, rolling and mountainous.
Soil, sandy, gravelly, and rocky, 3rd rate.
Timber, fir, pine, and hemlock.
Undergrowth, manzanita, chinquapin, snow brush, small fir and pine.

N. 0*02*W., bet. secs. 26 and 27 .

Over mountainous land, through scattering timber and dense undergrowth.

Asc. 150 ft. over SW. slope.

10.00 Enter thick growth of small timber, bears NE. and SW.
14.70 Spur, slopes W.; desc. 60 ft. over NW. slope.