

County Surveyor's Record, Douglas County, Oregon

Township 30 South 3 East.
Subdivision.

CHAINS

40.00 Set an iron post, 3 ft. long, 1 in. dia., 30 ins. in
the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ \text{S } 15 \text{ | S } 14 \\ 1928 \end{array}$$

from which

A fir, 6 ins. dia., bears N. 53*E., 5 lks.

dist., mkd. $\frac{1}{4}$ S 14 B T.

A fir, 6 ins. dia., bears S. 88*W., 45 lks.

dist., mkd. $\frac{1}{4}$ S 15 B T.

Asc. 115 ft. over broken SW. slope.

66.00 Spur, slopes W.; desc. 130 ft. over NW. slope to

80.00 Set an iron post, 3 ft. long, 2 ins. dia., 30 ins. in
the ground, for cor. of secs. 10, 11, 14, and 15,
with brass cap mkd.

$$\begin{array}{c} \text{T } 30 \text{ S } \text{R } 3 \text{ E} \\ \text{S } 10 \text{ | S } 11 \\ \text{S } 15 \text{ | S } 14 \\ 1928 \end{array}$$

from which

A fir, 20 ins. dia., bears N. 4*E., 14 lks.

dist., mkd. T 30 S R 3 E S 11 B T.

A fir, 10 ins. dia., bears S. 72 $\frac{1}{2}$ *E., 57 lks.

dist., mkd. T 30 S R 3 E S 14 B T.

A fir, 12 ins. dia., bears S 38 $\frac{1}{2}$ *W., 26 lks.

dist., mkd. T 30 S R 3 E S 15 B T.

A fir, 14 ins. dia., bears N. 36*W., 71 lks.

dist., mkd. T 30 S R 3 E S 10 B T.

Land, mountainous.

Soil, sandy, gravelly, and rocky, 3rd rate.

Timber, fir, pine, hemlock, and cedar.

Undergrowth, vine maple, huckleberry, small fir and pine.