

County Surveyor's Record, Douglas County, Oregon

Township 30 South, Range 3 East.

Subdivision.

CHAINS

Asc. 75 ft. over SW. slope.

11.20 Spur, slopes W.; desc. 60 ft. over NW. slope.

16.80 Draw, drains W.; asc. 40 ft. over broken W. slope to

40.00 Set an iron post, 3 ft. long, 1 in. dia., 30 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.

S 10 1/4 S 11
1928

from which

A fir, 15 ins. dia., bears S. 10* E., 21 lks. dist., mkd. 1/4 S 11 B T.

A fir, 7 ins. dia., bears S. 12* W., 6 lks. dist., mkd. 1/4 S 10 B T.

Asc. 210 ft. over SW. slope to sec. cor.

48.00 Enter dense 2nd growth timber, bears NW. and SE.

68.00 Enter heavy open timber, bears NW. and SE.

72.25 Spring branch, 1 1/4 wide, course W.

80.00 Set an iron post, 3 ft. long, 2 ins. dia., 30 ins. in the ground, for cor. of secs. 2, 3, 10, and 11, with brass cap mkd.

T 30 S R 3 E
S 3 S 2
S 10 S 11
1928

from which

A fir, 15 ins. dia., bears N. 25* E., 49 lks. dist., mkd. T 30 S R 3 E S 2 B T.

A fir, 36 ins. dia., bears S. 57* E., 42 lks. dist., mkd. T 30 S R 3 E S 11 B T.

A larch, 9 ins. dia., bears S. 46* W., 21 lks. dist., mkd. T 30 S R 3 E S 10 B T.

A fir, 36 ins. dia., bears N. 58* W., 34 lks. dist., mkd. T 30 S R 3 E S 3 B T.

Land, mountainous.

Soil, sandy, gravelly, and rocky, 3rd rate.

Timber, fir, pine, hemlock, cedar, and larch.