

County Surveyor's Record, Douglas County, Oregon

Township 30 South, Range 3 East.
Subdivision.

CHAINS

Undergrowth, huckleberry, hazel, small fir and pine.

From the cor. of Secs. 33 and 34 only, on S. bdy. of
the Tp.

N.0°02'W., bet. Secs. 33 and 34.

Over rolling land, through heavy timber and medium
undergrowth.

- 1.15 Left bank of the Rogue River, Course W.
2.87 Right bank of the river; asc. 35 ft. over SW. slope.
6.00 Spur, slopes W.; desc. 35 ft. over NW. slope.
15.25 Flat Creek, 30 lks. wide, Course W.
21.00 Asc. 85 ft. over SE. slope.
27.00 Spur, slopes E.; desc. 55 ft. over NE. slope.
28.85 Draw, drains E.; asc. 105 ft. over SE. slope.
35.90 Spur, slopes E.; desc. 60 ft. over NE. slope.
40.00 Draw, drains E.; asc. 20 ft. over S. slope to
42.00 Point 40.00 chs. in Southing from the cor. of Secs.
27, 28, 33 and 34, determined as hereinafter
described. At this point.
Set an iron post, 3 ft. long, 1 in. dia., 30 ins. in
the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ | \\ \text{S } 33 \quad | \quad \text{S } 34 \\ | \\ 1928 \end{array}$$

from which

A Fir, 18 ins. dia., bears S.37°45'E., 18 lks.
dist., mkd. $\frac{1}{4}$ S 34 B T.

A Hemlock, 20 ins. dia., bears N.20°30'W., 30 lks.
dist., mkd. $\frac{1}{4}$ S 33 B T.

Thence over broken E. slope.

- 50.70 Spring branch, 1 lk. wide, Course E.; asc. 180 ft.
over SE. slope.
62.85 Spur, slopes E.; desc. 150 ft. over NE. slope.
71.72 Spring branch, 1 lk. wide, Course E.; asc. 75 ft.