

66
County Surveyor's Record, Douglas County, Oregon

Township 30 South, Range 3 East.
Subdivision.

CHAINS

from which

A fir, .5 ins. dia., bears N.38*E., 35 lks.

dist., mkd. $\frac{1}{4}$ S 27. B T.

A fir, 20 ins. dia., bears S.64*W., 26 lks.

dist., mkd. $\frac{1}{4}$ S 28. B T.

Desc, 210 ft. over NE. slope.

63.63 Creek, 8 lks. wide, course E.; asc. 310 ft. over SE. slope.

76.15 Spur, slopes E.; desc. 40 ft. over N. slope to

80.00 Set an iron post, 3 ft. long, 2 ins. dia., 26 ins. in the ground, for cor. of secs. 21, 22, 27, and 28, with brass cap mkd.

T 30	S R 3 E
S 21	S 22
S 28	S 27
1928	

from which

A fir, 16 ins. dia., bears N. 29*E., 34 lks.

dist., mkd. T 30 S R 3 E S 22 B T.

A fir, 6 ins. dia., bears S. 71*E., 17 lks.

dist., mkd. T 30 S R 3 E S 27 B T.

A fir, 24 ins. dia., bears S.5 $\frac{1}{2}$ *W., 69 lks.

dist., mkd. T 30 S R 3 E S 28 B T.

A fir, 10 ins. dia., bears N.81*W., 33 lks.

dist., mkd. T 30 S R 3 E S 21 B T.

Land, mountainous.

Soil, sandy and gravelly, 3rd rate.

Timber, fir, pine, and hemlock.

Undergrowth, vine maple, huckleberry, small pine, fir, and hemlock.

East, on a random line bet. secs. 22 and 27.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.20 Intersect N. and S. line 20 lks. S. of the Cor. of secs. 22, 23, 26, and 27.