

8v
County Surveyor's Record, Douglas County, Oregon

Township 30 South, Range 3 East.

Subdivision

CHAINS

with brass cap mkd.

T 30 S R 3 E
S 17 | S 16
S 20 | S 21
1928

from which

A fir, 42 ins. dia., bears N. 2* E., 38 lks.
dist., mkd. T 30 S R 3 E S 16 B T.

A fir, 18 ins. dia., bears S. 63* E., 28 lks.
dist., mkd. T 30 S R 3 E S 21 B T.

A fir, 5 ins. dia., bears S. 84* W., 56 lks.
dist., mkd. T 30 S R 3 E S 20 B T.

A Fir, 6 ins. dia., bears N. 53* W., 9 lks.
dist., mkd. T 30 S R 3 E S 17 B T.

Land, mountainous.

Soil, sandy gravelly, and rocky, 3rd rate.

Timber, fir, pine, cedar, and hemlock.

Undergrowth, chinquapin, huckleberry, small fir, pine,
and cedar.

N. 89*52' E., on a random line bet. secs. 16 and 21.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.34 Intersect N. and S. line 20 lks. N. of the cor. of
secs. 15, 16, 21, and 22.

Thence

N. 89*59' W., on a true line.

Over mountainous land, through medium timber and dense
undergrowth.

Asc. 545 ft. over SE. slope.

32.00 Spur, slopes NE.; asc. 40 ft. over NE. slope to

40.17 Set an iron post, 3 ft. long, 1 in. dia., 30 ins. in
the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

S 16
 $\frac{1}{4}$
S 21
1928

from which