

County Surveyor's Record, Douglas County, Oregon

Township 30 South, Range 3 East.

Subdivision.

CHAINS

bears E. and W.

54.46 Creek, 1 lks. wide, course E.

56.44 Creek 4 lks. wide, course SE.; asc. 450 ft. over SW. slope to

80.00 Set an iron post, 3 ft. long, 2 ins. dia., 30 ins. in the ground, for cor. of secs. 8, 9, 16, and 17 with brass cap mkd.

T 30 S R 3 E  
S 8 S 9  
S 17 S 16  
1928

from which

A fir, 26 ins. dia., bears N. 9\* E., 81 lks. dist., mkd. T 30 S R 3 E S 9 B T.

A fir, 11 ins. dia., bears S. 32\* E., 23 lks. dist., mkd. T 30 S R 3 E S 16 B T.

A cedar, 9 ins. dia., bears S. 8\* W., 37 lks. dist., mkd. T 30 S R 3 E S 17 B T.

A fir, 28 ins. dia., bears N. 68\* W., 86 lks. dist., mkd. T 30 S R 3 E S 8 B T.

Land, mountainous.

Soil, sandy, gravelly, and rocky, 3rd rate.

Timber, fir, pine, hemlock, and cedar.

Undergrowth, rhododendron, chinquapin, huckleberry, small fir and pine.

S. 89\*59' E., on a random line bet. secs. 9 and 16.

40.00 Set temp. 1/4 sec. cor.

80.20 Intersect N. and S. line 7 lks. S. of the cor. of secs. 9, 10, 15, and 16.

Thence

S. 89\*58' W., on a true line.

Over mountainous land, through heavy timber and dense undergrowth.

Asc. 190 ft. over S. E. slope.