

County Surveyor's Record, Douglas County, Oregon

Township 30 South, Range 3 East

Subdivision.

CHAINS

- 2.00 Spur, slopes SE.; desc. 140 ft. over NE. slope.
- 14.16 Spring branch, 1 lk. wide, course E.; asc. 605 ft. over SE. slope to $\frac{1}{4}$ sec. cor.
- 30.32 Spring branch, 1 lk. wide, course SE.
- 40.00 Set an iron post, 3 ft. long, 1 in. dia., 30 ins. in the ground, for $\frac{1}{4}$ sec., with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ \text{S 8 | S 9} \\ 1928 \end{array}$$

from which

- A fir, 14 ins. dia., bears S. 51* E., 20 lks. dist., mkd. $\frac{1}{4}$ S 9 B T.
- A cedar, 14 ins. dia., bears N. 28* W., 83 lks. dist., mkd. $\frac{1}{4}$ S 8 B T.
- Asc. 235 ft. over S. slope.
- 47.70 Ridge, bears NE. and SW.; leave green timber and enter an old burn, bears E. and W., dead standing and fallen timber, desc. 270 ft. over NW. slope.
- 53.25 Forest Service trail, bears N E. and SW.
- 70.75 A rocky draw, drains W.; asc. 205 ft. over S. slope to
- 80.00 Set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in the ground, for cor. of secs. 4, 5, 8, and 9, with brass cap mkd.

$$\begin{array}{c} \text{T 30 S R 3 E} \\ \text{S 5 | S 4} \\ \text{S 8 | S 9} \\ 1928 \end{array}$$

No bearing trees available. Build a mound of stone, 4 ft. base, 2 ft. high. 4 lks. W. of cor.

A cross (X) and B O cut on a 14 x 18 in. flat face of a broken ledge, facing the cor., bears N. 23* E., 23 lks. dist.

Land, mountainous.

Soil, sandy, gravelly, and rocky, 2nd rate.

Timber, fir, pine, cedar, and hemlock.

Undergrowth, vine maple, hazel, small fir and pine,